




|                          |                            |
|--------------------------|----------------------------|
| <b>MALZEME</b>           | Bakır (E-Cu), Kalay Kaplı  |
| <b>İZOLASYON</b>         | PVC                        |
| <b>ÇALIŞMA SICAKLIĞI</b> | Maksimum 75 °C<br>600 Volt |



## YUVARLAK TİP İZOLELİ KABLO UÇLARI

DIN 46237

| KABLO KESİTİ (mm²) | ÜRÜN KODU   | RENK | CİVATA M | BOYUTLAR |      |      |     |     |      |     | KUTU İÇERİĞİ | KOLİ İÇERİĞİ | KUTU AĞIRLIĞI (gr) |
|--------------------|-------------|------|----------|----------|------|------|-----|-----|------|-----|--------------|--------------|--------------------|
|                    |             |      |          | l        | d2   | d3   | d1  | d4  | a    | s   |              |              |                    |
| 0,50-1,50          | YK-301KPVC  |      | M3       | 16,5     | 3,2  | 6,0  |     |     |      |     |              |              | 182                |
|                    | YK-401KPVC  |      | M4       | 17,5     | 4,3  | 8,0  |     |     |      |     |              |              | 206                |
|                    | YK-501KPVC  |      | M5       | 18,5     | 5,3  | 10,0 | 1,6 | 4,0 | 10,5 | 0,8 | 200          | 12000        | 238                |
|                    | YK-601KPVC  |      | M6       | 22,5     | 6,5  | 10,0 |     |     |      |     |              |              | 255                |
|                    | YK-801KPVC  |      | M8       | 22,5     | 8,4  | 14,0 |     |     |      |     |              |              | 324                |
| 1,50-2,50          | YK-302MPVC  |      | M3       | 17,0     | 3,2  | 6,0  |     |     |      |     |              |              | 202                |
|                    | YK-402MPVC  |      | M4       | 18,0     | 4,3  | 8,0  |     |     |      |     |              | 12000        | 224                |
|                    | YK-502MPVC  |      | M5       | 20,0     | 5,3  | 10,0 |     |     |      |     | 200          |              | 269                |
|                    | YK-602MPVC  |      | M6       | 21,0     | 6,5  | 11,0 | 2,3 | 4,5 | 11,0 | 0,8 |              | 10000        | 297                |
|                    | YK-802MPVC  |      | M8       | 22,5     | 8,4  | 14,0 |     |     |      |     |              |              | 346                |
|                    | YK-1002MPVC |      | M10      | 25,5     | 10,5 | 18,0 |     |     |      |     | 100          | 5000         | 253                |
| 4,00-6,00          | YK-1202MPVC |      | M12      | 25,5     | 13,0 | 18,0 |     |     |      |     |              | 6000         | 200                |
|                    | YK-406SPVC  |      | M4       | 21,0     | 4,3  | 8,0  |     |     |      |     |              |              | 205                |
|                    | YK-506SPVC  |      | M5       | 22,5     | 5,3  | 10,0 |     |     |      |     |              | 6000         | 223                |
|                    | YK-606SPVC  |      | M6       | 23,5     | 6,5  | 11,0 | 3,6 | 6,3 | 13,5 | 1,0 | 100          |              | 249                |
|                    | YK-806SPVC  |      | M8       | 26,5     | 8,4  | 14,0 |     |     |      |     |              | 5000         | 290                |
|                    | YK-1006SPVC |      | M10      | 28,5     | 10,5 | 18,0 |     |     |      |     |              |              | 351                |
|                    | YK-1206SPVC |      | M12      | 28,5     | 13,0 | 18,0 |     |     |      |     | 50           | 3000         | 172                |

\* Tüm ölçüler milimetre (mm) cinsindendir.

\* Şafak, ürün özelliklerinde önceden bildirimde bulunmaksızın değişiklik yapma hakkını saklı tutar.